



Blue Reef Water Solutions (Pty) Ltd Reg No 2013/149985/07; Tel. +27 31 910 7500 ;
PO Box 32079, Mobeeni, 4060, KwaZulu-Natal, South Africa

BDA-L70 HPI

MULTI-PURPOSE SPECIALISED ANTISCALANT

TYPE – Specialised High Performance Dispersant and Antiscalant for Boiler Internal Treatments, Evaporators, Reverse Osmosis Systems, Cooling Systems and Process Waters such as Mining, Iron and Steel, Paper & Pulp, Sugar Processing and Critical Heat Exchange Operations.

BDA-L70 HPI is a specialized reacted polymer containing polymeric anti-scalants, sequestrants and dispersants. It is designed to inhibit precipitation of calcium, magnesium and iron salts in the form of carbonate, sulphate, phosphate and silicate compounds.

TYPICAL PROPERTIES

Appearance	:	Clear/Opaque Straw Coloured Liquid
Flash Point	:	Not Applicable
pH at 25°C	:	7.0-10.0
Specific Gravity at 25°C	:	1.10-1.15
Solubility in Water	:	Complete



The data contained herein is believed to be accurate and reliable. However, neither the above named supplier nor any of its subsidiaries assume any legal liability whatsoever for the accuracy or completeness of information contained herein. Users should undertake sufficient verification and testing to determine the suitability for their own purposes of any product or information contained herein. Recommendations are given in good faith but without warranty and subject to the exclusion of any liability.



APPLICATION & CONTROL

BDA-L70 HPI is dosed as follows :

Dosage required will vary according to the potential precipitative salts present and a detailed analysis of the process water is recommended. Dosages may range from 5mg/l through 25mg/l in make-up and/or feed dependent upon cycles of concentration and/or application. On line cleans will warrant higher dosages.

BDA-L70 HPI is used as REVERSE OSMOSIS MEMBRANE TREATMENT; COOLING SYSTEM/PROCESS DISPERSANT or as a BOILER DISPERSANT ADDITIVE and as an adjunct to the boiler internal treatment programmes such as – BIT-L50-HP as an extra additive when boiler water exhibits high suspend solid conditions or when scaling conditions are prevalent. It is also used extensively when boilers are being brought on line or taken off line at regular intervals.

Please refer to FDA acceptance and declaration sheet.

STORAGE AND HANDLING

BDA-L70 HPI can be stored for up to 24 months from the date of manufacture, in its original, sealed packaging, at room temperature in a dry area. Containers must be kept undercover and out of direct sunlight. This product can be safely stored in plastic type holding tanks designed to manage the specific gravity listed. **BDA-L70 HPI** must be protected from freezing. Protective clothing such as gloves and goggles should be worn when handling.

HEALTH AND SAFETY

BDA-L70 HPI is of low toxicity and any residue monomers present have low toxicity. The product is relatively neutral but eye contact or prolonged skin contact may cause irritation. Should contact occur, hands should be washed with soap and water and eyes well irrigated for fifteen minutes. Ingestion will induce vomiting and should be treated symptomatically. Spillages must be contained to allow for safe disposal. Avoid direct flushing to storm water drain. Please refer to product SAFETY DATA.



The data contained herein is believed to be accurate and reliable. However, neither the above named supplier nor any of its subsidiaries assume any legal liability whatsoever for the accuracy or completeness of information contained herein. Users should undertake sufficient verification and testing to determine the suitability for their own purposes of any product or information contained herein. Recommendations are given in good faith but without warranty and subject to the exclusion of any liability.



The data contained herein is believed to be accurate and reliable. However, neither the above named supplier nor any of its subsidiaries assume any legal liability whatsoever for the accuracy or completeness of information contained herein. Users should undertake sufficient verification and testing to determine the suitability for their own purposes of any product or information contained herein. Recommendations are given in good faith but without warranty and subject to the exclusion of any liability.