

PRODUCT & TECHNICAL DATA

FC200

FUEL OIL CONDITIONER

**PREPARED & READY TO USE FOR
IMPROVEMENT OF COMBUSTION**

FC 200 promotes dispersion of heavy hydrocarbons, carbon, water and other sludge and deposit-forming substances, improves combustion and atomization of the oils, reduces corrosion of metals in contact with the fuel, and is a highly relevant agent for gas sweetening due to its ability to **remove hydrogen sulfide**. This results in fewer deposits and improved system efficiency due to better flow and combustion.

FC 200 will also remove deposits gradually in fuel tanks and lines containing heavy deposits.

**CLEANER
COMBUSTION**

**BETTER
PERFORMANCE**

**GREATER
EFFICIENCY**

**Product
info**



TYPICAL PROPERTIES

	APPEARANCE	Clear to Slightly Opaque Greenish Liquid
	FLASH POINT	Flash Point Indicated at between $>64^{\circ}\text{C}$ & $<95^{\circ}\text{C}$
	pH AT 25°C	Not Applicable – solvent based
	SPECIFIC GRAVITY AT 25°C	0.85 – 0.99 typical
	SOLUBILITY IN WATER	Dispersible and Miscible



APPLICATION & CONTROL

FC 200 is typically dosed on a regular basis to the bulk storage prone to organic and microbiological contamination.

This dosage may be undertaken via a proportional dosing pump or slug dosed at

**1 LITRE FC 200
PER 2000L TO 3000L
OF FUEL OIL.**

For heavily fouled or contaminated systems, the dosage should be

**1 LITRE PER 750L TO 1000L
OF FUEL OIL.**



**IMPROVES
COMBUSTION &
ATOMIZATION**



**REDUCES
CORROSION
& WEAR**



**DISPERSES
SLUDGE,
CARBON & WATER**



**ENHANCES
EFFICIENCY &
PERFORMANCE**



Blue Reef Water Solutions (Pty) Ltd
Gate 2 Unit 7 (B3/U1),
New Germany Industrial Park,
9 Chelsea Ave, New Germany, 3610



+27 82 774 6864



info@bluereef.co.za



www.bluereef.co.za